

Sign in

Patents

Find prior art


Discuss this patent

View PDF

Download PDF



Adjustable electrical phaseshifting network US 2623945 A

ABSTRACT [available in](#)**IMAGES** (2)

Publication number	US2623945 A
Publication type	Grant
Publication date	30 Dec 1952
Filing date	9 May 1946
Priority date	9 Jan 1945
Inventors	Ramsay Wigan Edmund
Original Assignee	Int Standard Electric Corp
Export Citation	BiBTeX , EndNote , RefMan
Patent Citations (11), Referenced by (6), Classifications (9)	
External Links: USPTO , USPTO Assignment , Espacenet	

DESCRIPTION (OCR text may contain errors)**CLAIMS** [available in](#)

Dec. 30, 1952 E. R. WIGAN 2,623,945

ADJUSTABLE ELECTRICAL PHASE-SHIFTING NETWORK Filed May 9, 1946 2 SHEETS-SHEET 1 F/GI. F/G.2. 5 6 s 6 1
INVENTOR Z: 4 IpMdn/P KAMSAY Dec. 30, 1952 E. R. WIGAN 2,623,945

ADJUSTABLE ELECTRICAL PHASE-SHIFTING NETWORK Filed May 9, 1946 2 SHEETS-SHEET 2 Y F/ G. 5. W Y

CURVEa r, ZERO b SMALL mu: fb c r, GRIT/CA4 mus d r ZARGE VALUE F/G. 6

Q? 3 fa 2 to i 3 3 g z E m g g "R N E 1 Q X o s P x 0 05, K v H /N I/E N TOR E unwvp EMMY Nisan ATTORNEY Patented
Dec. 30, 1952 UNITED STATES T ()FFICE ADJUSTABLE ELECTRICAL PHASE- SHIFTING NETWORK of Delaware
Application May 9, 1946, Serial No. 668,610 In Great Britain January 9, 1945 Section 1, Public Law 690, August 8, 1946
Patent expires January 9, 1965 6 Claims.

The present invention relates to electrical" phaseshifting networks, with particular reference to networks which may be conveniently ad- 1 .iusted'to produce a zero phase shift at any desired frequency in a-given range of frequencies.

The invention is of particular advantage when applied to the frequency determining network of an oscillator of "the resistance-reactahce type, which includes a coupling network of the L type, having a series arm and a'shunt arm both of which include resistive and reactive elements, the frequency of oscillation being substantially that for which the phase shift'produced by the net work is zero. Such .a. network may also be used in frequency meters.

As will be explained more fully later, in the present invention an adjustable impedance element is added to the conventional L network oi the resistance-reactance type, .andby means of this adjustable element, the frequency of zero phase shift may be varied over a certain range, while the network may also be designed so that the voltage transfer ratio of the network at the frequency of zero phase shift is independent of the frequency, and is determined by the series and shunt arms of "the :network. This is a valuable property of the invention because it enables the frequency of an oscillator to be varied without varying the output level, and, further if the adjustable impedance element be adapted to be varied in some way under the control of a signal for example, if the element should be a microphone) substantially pure frequency modulation unaccompanied by amplitude modulation will be obtained in a very simple manner.

The invention accordingly provides an electrical phase shifting network including resistive and reactive impedance elements arranged in series and shunt arms of the network, and comprising an additional impedance element connecting a point in a series arm with a point in a shunt arm,

the arrangement being such that the phase shift produced by the network is zero at a frequency which depends on the magnitude of the additional element.

The invention will be described with reference to the accompanying drawings, in which:

Fig. -1 shows a schematic circuit diagram of a known type of phase shifting network;

Fig. 2 shows the network of Fig. 1 modified according to the invention, to give one example illustrating the invention;

Fig. 8 shows a block schematic diagram of the most general network according to the invention; r

, Fig. 4 shows a schematic circuit diagram which includes a group of networks according to the invention;

Figs. 5 and 6 show characteristic curves of networks according to the invention;

of particular networks according to the invention;

Fig. 11 shows a schematic circuit diagram of an oscillator incorporating a network according to the invention; and

Figs. 12 and 13 show modifications of the networks of Fig. 2.

Fig. 1 shows a coupling network of well-known type often employed in a resistance-reactance type of oscillator. The input terminals 1, 2 are connected to the output terminals 3, 4 by a series arm including a condenser 5 in series with a resistance 6, and a shunt arm including a condenser 7 in parallel with a resistance 8. Fig. 2 shows one particular example of a network according to the present invention, and is the same as Fig. 1 with the addition of a resistance 9 (which may be variable) connecting a point in the resistance 6 with a point in the resistance 8. It can be shown that by proper proportioning of the elements of the network, the phase shift between the terminals 1, 2 and the terminals 3, 4 can be made zero at a particular frequency, and moreover, if the resistance 9 be made adjustable, the frequency of zero phase shift may be varied over a certain range. In addition, the elements of the network may be so designed that the voltage transfer ratio, that is, the ratio of the output voltage to the input voltage, at the frequency of zero phase shift, is constant.

Fig. 2 is, however, only one possible form of the network according to the invention, which is indicated more generally in Fig. 3. The series arm includes two series impedances represented by blocks I2 and I3, and the shunt arm includes two impedances I4 and I5 connected in series, and shunted by another impedance I6, still another impedance I7 being connected in series with the combination of I4, I5 and I6. The adjustable impedance I6, which is the principal characteristic of the invention, is connected between the junction points of impedances I3 and I4 and impedance I2 and I5.

some of the blocks in to 15 may include both resistance and reactance elements; and the series and shunt arms of the network must each of them include at least one resistance element and at least one reactance element. The impedance I6 can be either a variable resistance or a variable reactance. The impedance I7 is not an essential element and may be omitted, but when used will generally be a resistance element. It will be understood, of course, that reactance elements may be condensers or inductances. Usually, also, the impedances I1, I2, I3 and I4 will be all of the same kind, that is, they will be all resistances, or all reactances of the same sign.

It will be understood, also, that the networks included in Fig. 3 can generally be replaced by equivalent networks with the elements arranged in other ways, according to well known principles.

The elements of the network of Fig. 3 may be designed to fulfil desired conditions by solution of the network according to well known principles, but the general solution is involved and tedious, and accordingly the solution in one or two typical cases will be quoted. It is always assumed that the impedance to which the terminals 3 and 4 are connected is substantially infinite.

In the particular case of Fig. 3 shown in Fig. 4, A

the impedance I9 consists of an element of reactance X1 in series with a resistance r1. The

impedance I6 consists of an element of reactance X2 in series with a resistance m. The impedances I1, I2, I3, I4 and I5 are resistances y, a, b, r1 and P respectively. It will be understood that the reactances X1 and X2 may be represented either by condensers or by inductances.

The following additional symbols will be used:

K: $(P+a+y)/(a+y)$ Voltage transfer ratio $e_2/e_1=L$;

It follows that $BM = d$ It will be first assumed that $r_2=0$ Then it can be shown that the condition for zero phase shift is In practice it is usually desirable to be able to choose the value of the voltage transfer ratio L. It can be shown that at the frequency of zero phase shift, and when the network elements have been chosen so that L is the same at all such zero-phase-shift frequencies,

Equation 1 may then be written in a slightly different form using Equation 2 The frequency of zero phase shift may be determined from Equation 1 or 3 since it occurs in the reactances X1 and X2. For example if f is this frequency and if X1 and X2 are represented by condensers of capacities C1 and C2 then if X1 and X2 are represented by inductances L1 and L2, then $X_1 X_2 = 4 = 1/r f L_1 L_2$ It will be noted from Equation 1 that when P is infinite, then the corresponding limiting value of the zero-phase-shift frequency is that frequency for which When P is zero the corresponding limiting value of the zero-phase-shift frequency is that frequency for which From Equation 3, since $K = 1$ when $P=0$.

Equation 7 indicates that when X1 and X2 are negative reactances, 11 may be chosen so that the limiting zero-phase-shift frequency is infinite when $P=0$. Likewise when X1 and X2 are positive reactances r1 may be chosen so that the limiting zero-phase-shift frequency is zero when $P=0$. In both cases, of course, $X_1 X_2$ is zero.

It is not practicable to give any very definite directions as to the choice of values for the elements of the network to fulfil specified conditions, because the possibilities of choice are rather wide and the procedure will often be determined by such factors as the limitations set by the design or availability of certain of the elements. However, the process may be somewhat as follows:

When designing a network to cover a certain frequency range the first step is to choose a value of L which is suitable for

the circuit associated with the network; for example, when the network is used in an oscillator, the value of L will be determined at least in part by the gain of the associated amplifier.

The parameters M , N and A are then chosen to satisfy Equation 2. Unless a wide range of variation of the zero-phase-shift frequency by adjustment of P is required, A may be made zero by making r_1 zero. The tapping points to which the resistance P are to be connected are determined from Equation 4 or 5 from which d is found, and therefore B may be determined, since M has been already fixed.

Any value of 20 may now be selected, and from the value of B just determined the corresponding value of q is found. If a wide range of variation of the zero-phase-shift frequency is desired, a large value of p should be chosen. All the quantities in Equation 1 are now fixed except the individual values of $X_1Z_1R_1$ and R_2 .

Let it be assumed that X_1 and X_2 are produced by condensers C_1 and C_2 . Then the lowest frequency of the range will be obtained for the maximum practicable value of P , and the highest frequency when $P=0$. A trial choice of values of R_1 , B_2 , C_1 and C_2 should be made on the assumption that P is disconnected, in order to obtain the lowest desired zero-phase-shift frequency. If R_2 can conveniently be given a value small compared with the highest practicable value of P , then this lowest frequency will not be much affected when P is connected and set to its maximum value. A suitable value of y_e may now be found from Equation 1 in order to obtain the highest desired zero-phase-shift frequency when P has its smallest practicable value. Then q is determined from the value of B as already mentioned.

The manner in which the performance of the network of Fig. 4 (in which the reactances X_1 and X_2 are represented by condensers) depends on the value of the resistance 11 is shown in Fig. 5, in which the zero-phase-shift frequency f is plotted against the value of P . The curve (or) represents the case when $r_1=0$, and is asymptotic to a line QR parallel to OK , which line cuts the axis OY at the point Q representing the minimum value of 1 when P is infinite. The curve (a) cuts the axis OY at a point corresponding to the minimum zero-phase-shift frequency f_a when $P=0$. When 11 has a small value, the corresponding curve (b) lies above the curve (a) and cuts the axis OY at a point corresponding to a higher maximum frequency f_b .

The curve represents the special critical case when the value of n has been chosen so that f is infinite when P is zero. This curve is asymptotic to OY .

The curve (1) shows the case when n has a value larger than the critical value. This curve is asymptotic to a line ST parallel to CY and cutting the axis OX in a point S corresponding to the minimum value of P for which any zero-phase-shift frequency is possible.

It will be evident from Equation 6 that each of the curves (a), (b), (c), (d) will be asymptotic to a different line parallel to OK . Only the line QR corresponding to curve (a) has been shown, in order to avoid confusing the figure.

It should be pointed out that the degree of separation of the curves (a), (b), (c), (d) depends on the value of p which has been selected. When a relatively large value of p is chosen, the curves are well separated, as shown in Fig. 5, but for smaller values, the curves (b), (c) and (d) tend to move closer together, and to curve (a), and as p approaches zero they will all tend to coincide with curve (a). The curves of Fig. 5 also represent the case in which the reactances X_1 and X_2 are provided by inductances, so long as the scale of ordinates along OY is in terms of $1/\omega$ instead of in terms of ω .

When all the elements of the network have been selected, the Equation 3 may be written in the form $f = A_2A_4/K$ where $A_1A_2A_3$ and A_4 are constants, the forms (a) and (1) corresponding respectively to the cases in which the reactances X_1 and X_2 are provided by condensers and inductances.

Equations 8 show in the simplest form the relation between P (which is contained in K) and the corresponding zero-phase-shift frequency.

Fig. 6 shows $1/f$ for Equation 8(a) (or f for Equation 8(1)) plotted against $1/P$ for the case in which $1'$ is larger than the critical value (curve (5), Fig. 5). The curve is a straight line cutting the axis OX and OY in V and W such that $OW:A_1$ (or A_3) and the tangent of the angle OVW is A_2 (or A_1). The value OV or $1/K$ for infinite (or zero) zero-phase-shift frequency is less than 1 , so that f has a minimum value corresponding to OS in Fig. 5. If the critical value of $1-1$ is chosen (curve (c), Fig. 5), then the point V in Fig. 6 will be such that $OV=1$, and the whole of the range of P can then be used. This condition leaves Equations 4 and 5 unchanged.

In this case the various parameters may be chosen in a manner similar to that explained above.

The equations corresponding to Equations 6 for the limiting zero-phase-shift frequency when P is infinite are It will be understood that although for convenience the cases in which $r_1=0$ and $r_2=0$ have been treated separately, networks may be used in which neither r_1 nor r_2 is zero.

It has already been pointed out that the reactances X_1 and X_2 of Fig. 4 may be positive or negative. Another series of networks according to the invention may be obtained by replacing the reactances X_1 and X_2 by resistances and the resistances 31 , y , a , b and P by reactances all of the same kind.

Fig. 7 shows a typical example of one of these networks using capacitive reactances. The series arm of the network comprises a resistance 11 connected in series with two condensers 12 and 13 , and the shunt arm comprises a resistance 26 in parallel with two series connected condensers 21 and 22 . A variable condenser 23 is connected between the junction point of the condensers 13 and 19 and the junction point of the condensers 21 and 22 .

A resistance $T1$ (not shown) could be connected in series with the whole of the shunt arm (in the manner shown in Fig. 4)

if the performance indicated by curve (b), (c) or (d) of Fig. 5 is required. Alternatively a condenser (not shown) having a reactance D times the reactance of the condensers Z_1 and Z_2 taken in series, may be connected in series with the resistance 2% to give the performance just referred to, or both the resistance and the condenser may be provided.

For the network of Fig. '7, Equation 1 will be modified as follows:

Equation 4 is changed as follows;

$1/L:1+BN-\{M/(1+EN)\}$ (14) Equation 2 will be unchanged.

8 shows another circuit according to the invention, which can be shown by well known network transforming methods to be identically equivalent to the circuit of Fig. '2. It will be noted that Fig. '8 differs from Fig. 2 in that the upper end of the shunt resistance 8 is connected to the opposite end of the series resistance '6. If the capacities of condensers 5 and '1 in Fig. 8 are respectively equal to the capacities of condensers 7 and 5 in Fig. 2, then both networks have the same relation between the value of P and the zero-phase-shift frequency, but the value of L is different unless the capacities of condensers 5 and 1 are equal in each network. All the networks covered by 4 can be transformed in a similar way.

It may be pointed out that the networks including condensers are suitable for high frequencies. Then there is always a finite lower limit to the zero-phase-shift frequency, but the upper limit, which occurs when P approaches zero, can be made infinite if suitably proportioned resistances r_1 and r_m be included. Likewise those including inductances are more suitable for low frequencies. Then there is always a finite upper limit to the zero-phase-shift frequency, but the lower limit, which occurs when P approaches zero, can be made zero by means of the resistances r_1 and/or r_2 .

It should be noted, also, that the zero-phase-shift frequency can be adjusted in an alternative manner, namely by keeping P fixed and simultaneously varying the tapping points on the series and shunt arms of the networks in such manner that p and q fulfil the conditions of Equation 4 or 14.

This is quite a practical scheme when the ele- As it may be inconvenient to divide the series 3' and shunt impedance elements of the network in order to obtain the tapping points for the adjustable element P , the same result may be achieved in a different way, an example of which is shown in Fig. 9 which is a modification of Fig. '7. In Fig. 9 the condenser 24 replaces the two condensers 18 and 19 of Fig. 7, and is shunted by two other condensers 25 and 26 connected in series. Likewise the condenser 21 replaces the two condensers 21 and 22 of Fig. 7 and is shunted by the two condensers 28 and 29 connected in series. The condenser 23, which represents the variable element P , is connected between the junction points of the condensers 25 and 25 and of the condensers 28 and 29 respectively. The capacities of the condensers 24, 25 and 26 will be chosen so that if the deltas 24, 25, 26 and 21, 23, 29 be supposed replaced by the equivalent '1 arrangements, the capacities of the T which act effectively in series with the resistance 1 are respectively equal to the capacities of condensers 18 and 19 of Fig. '7. Similarly the effective series capacities of the T network equivalent to the delta 21, 28, 29 should be respectively equal to the capacities of the two condensers 21 and 22.

The arrangement then operates in the same way as that of Fig. '7, except that an additional reactance contributed by the shunt arms of the equivalent T networks acts effectively in series with the variable element 23, so that this additional reactance must be included in the value of P , and sets a limit to its minimum value.

A similar delta arrangement can evidently be used in a network similar to Fig. 2 in which each of the resistances 6 and 8 could be shunted by a tapped resistance, the resistance 9 being connected between the two taps. The values of the resistances would be chosen according to the same principles as in Fig. 9. Clearly, also an arrangement similar to Fig. 9 could be used in which all the condensers are replaced by inductances.

It is evident also, that the delta arrangement could be used, if desired, for only one of the arms of the network.

This delta arrangement may be found convenient in order to avoid tapping a precision element. Thus in Fig. 9, the condensers 24 and 27 may be high grade adjustable condensers in order to provide a number of different frequency ranges. In such a case tapping these condensers would be impracticable, and the additional condensers such as 25 and 26 can conveniently be provided with the proper capacity ratio, and would not need to be changed when the condenser 24 is changed. This device is also useful in other circumstances, an example of which occurs in Fig. 12.

Referring again to Fig. 3, the introduction of the impedance [5 may be treated in a slightly different manner. Suppose that the elements 11 to M and 16 have been designed according to the principles already explained so that a constant voltage transfer ratio at the zero-phase-shift frequency, determined by the adjustment of element [6, has been obtained. Then for given setting of this element, the network is equivalent to the portion inside the dotted outline of Fig. 10, which consists of a series impedance Z_1 and a shunt impedance Z_2 whose values can be calculated according to well known principles from the values of the elements in to M and 16 . The voltage transfer ratio L will be $Z_2 / (Z_1 + Z_2)$ which, as already stated, will be constant at the zero-phase-shift frequency for adjustments of the element 16 . If now the element 15 of impedance Z_4 be introduced in series with Z_2 , then the voltage transfer ratio of the whole network of Fig. 10 will still be equal to L provided with an impedance Z_3 is introduced in series with Z_1 , as shown, having the value $(1-L)Z_4/L$. The relation between the value of P and the zero-phase-shift frequency will be unchanged. It will be understood that Z_3 and Z_4 can be any type of impedances whatever, provided that their ratio is $(1-L)/L$ independent of frequency. Thus, for example, if Z_4 comprises an inductance L_0 in parallel with a series combination of a condenser of capacity C_0 and a resistance R_0 , then impedance Z_3 will be an inductance μL_0 in parallel with a series combination of a condenser of capacity $C/$ and a resistance μR_0 . It is evident that Z_3 and Z_4 could comprise single impedance elements of any type, or any kind of network of such elements.

It will be understood that the impedances Z_3 and Z_4 may be introduced in this manner whether or not '7'2 is included in the

shunt arm or" the original network, and whatever be the form of the original network. The value of L to be used is in all cases that of the original network before Z3 and Z4 have been introduced.

When, as in the case first treated above, the impedance Z4 is a resistance T1 and when no corresponding impedance Z3 is included in the series arm, then the relation between P and the zero-phase-shift frequency is affected by T1, according to Equations 1 and 3 and the curves shown in Fig. 0.

in order further to illustrate the invention, some particular cases will be quoted. A simple case of Fig. 2 is that for which.

From Equation 2 it follows that $L = \frac{P}{\omega}$. If q is chosen equal to zero, so that the variable resistance P is connected to the junction point C and R in the series arm, then it follows from Equation 4 or that $p = 0.618$.

It can be shown from Equation 1 by putting $P=0$ and $P=\infty$ therein, that the ratio of the maximum to the minimum zero-phase-shift frequency is 2.618.

P (ohms) f (O./S.)

This simple case gives a rather small total variation of the zero-phase-shift frequency, and as already explained, the introduction of a suitable resistance T1 will enable this range to be extended to infinity. A suitable value of H can be obtained by solving Equation 1 for A when the left hand side is put equal to zero.

In the particular case in which $R_1=R_2=R$; and $C_1=C_2=C$; $L_2=0$; the values of p and q were and respectively. This gives an infinite zero-phase-shift frequency for $P=0$; and the corresponding value of L is 0.4. It can be seen from Equation 1 or 3 that the zero-phase-shift frequency for $P=\infty$ is given by $1/f = \sqrt{2} + rRC$. For the special case in which $R=1065$ ohms $1/C$ (ohms) $995,000$ 361 f(C./S.) $1,360$ $1,6.5'3,000$

If in this case a compensating resistance Z3 for T1 be included in the series arm in the manner explained with reference to Fig. 10, the value of L for the network without n is now (from Equation 2 since $A=0$) so $\mu = 2$, and the value of Z3 should be $2r = 708$ ohms. The zero-phase-shift frequency for $P = 0$ will however not be infinite, since n no longer affects the frequency characteristic.

Two numerical examples will be given for the network of Fig. 4; in the first of which X1 and X2 are negative reactances represented by condensers of capacities C1 and C2, and in the second of which K1 and X2 are positive reactances represented by inductances L1 and L2.

The following measured values of the zero-phase-shift frequency f_1 were obtained for various values of P:

The value of L when r is about 480 ohms, so that smaller values of P cannot be used.

Case 2 $R_1=1100$ ohms $10:0.835$ $R_2=1053$ ohms $q=0.030$ $L_1=0.206$ henry $M=1.043$

$232:0.728$ henry TIF-TO $r_2=120$ ohms A final numerical; example of Fig. 7 will be given:

R_1 (resistance of $1'$) $=2000$ ohms R_2 (resistance of $20'$) $=1000$ ohms C_1 (capacity of $19'$) $=0.114$ f.

Element 18 was short-circuited, so

The following measured values of the zero-phase-shift frequency are obtained for various values of the capacity Cs of the condenser 23:

0 en.) 0 691 Fig. 11. shows an oscillator circuit employing one of the networks according to the invention. The arrangement of Fig. 4 in which the reactances X1 and X2 are represented by inductances L1 and L2 is particularly convenient for this purpose, and results in a very simple circuit. In Fig. 11 a thermionic valve 30 has a resistance 31 connected in series between the cathode and ground. The anode is connected through a suitable anode resistance 32 to the positive terminal 33 for the high tension supply source (not shown), the grounded negative terminal of which is 3. The output oscillations may be taken from terminal 35 connected to the anode through a blocking condenser 36.

The cathode circuit of the valve is connected to the control grid circuit by a network according to the invention comprising a series arm including an inductance coil 31 (L1) and a tapped resistance 38 (R1) and a shunt arm including an inductance coil 39 (L2) and a tapped resistance i_0 (R2), a resistance 41 (r2) being shown connected in series with the inductance coil 39. It will be understood that the resistance 41 includes the resistance of the coil 39 and may not be represented by any actual element.

The inductance coil 39 is also the primary winding of a transformer, the secondary winding 52 of which is connected to a high resistance potentiometer 43 and has one terminal connected to ground. The adjustable contact of the potentiometer 43 is connected to the control grid of the valve 30. An adjustable resistance M (P) is connected between the tapping points on the resistances 38 and 41.

The transformer formed by the coils 39 and 52 may have a step-up ratio of the order of 3:1, and the potentiometer 43 should have a very high resistance so that the inductance L2 is substantially the primary inductance of the transformer.

Since there is substantially a zero phase change between the control grid and cathode of an amplifying valve arranged in the manner of Fig. 11, oscillations will occur at the zero-phase-shift frequency of the coupling network.

It will be clear, therefore, from what has been explained, that the network may be designed to obtain any desired range of oscillation frequencies by adjustment of the single resistance element 44; and moreover, the amplitude of the oscillations

may be made practically independent of the frequency. The value of L for the network should be chosen suitably in relation to the transformer ratio and to the gain of the amplifier, and the potentiometer 43 provides a convenient fine adjustment for L to enable the oscillation condition to be correctly set.

It will be understood that the output may be taken from the valve 30 in various other ways. For example, a separate amplifying valve (not shown) may be provided, with its control grid (or cathode) connected directly to the control grid (or cathode) of the valve 33. In this case the resistance 32 and condenser 36 will not be needed.

Attention is however drawn to the fact that the conditions for constant voltage transfer ratio L are only approximately fulfilled in the circuit of Fig. 11 because of the presence of the resistance T2 in series with L2. The voltage applied to the control grid of the valve 30 should ideally be proportional to the voltage across the resistance 40, but it will be seen that in Fig. 11, the voltage applied to the control grid is proportional to the voltage across L2, which is slightly different on account of the presence of m. However, if m is small, and/or the range of variation of the element 44 is small, the value of L will vary only slightly as this element is adjusted.

As already mentioned, the circuit of Fig. 11 provides a particularly simple oscillation circuit. However, any of the other networks which have been described may be used to couple the cathode to the control grid of the valve 30, with the bias and other operating arrangements for the valve modified where necessary, as will be understood by those skilled in the art. A step-up transformer will be required between the output of the network and the control grid, because the voltage amplification factor of the valve 30 arranged as a cathode follower is always less than 1. Such a transformer should be designed to have a very high primary impedance otherwise an appreciable phase shift may be introduced which might result in a corresponding small variation in the voltage transfer ratio. It is however the particular advantage of the network shown in Fig. 11 that the primary winding of this transformer can form an integral part of the network.

It will be understood also, that any of the networks according to the invention may be used in the usual two-valve resistance reactance oscillator circuits in which the anode of each valve is coupled to the control grid of the other, one of the couplings including the network which determines the frequency.

Owing to the fact that the oscillation amplitude can be independent of the frequency, an oscillator employing a network according to the invention may be very easily used to produce frequency modulated waves without any accompanying amplitude modulation. Thus, for example, in an oscillation circuit employing any of the networks of Fig. 4, the element [6 need only be replaced by a carbon microphone, the resistance of which, as is well known, varies in accordance with the pressure of the sound waves which impinge on the diaphragm. The circuit being designed to generate a suitable carrier frequency, the output waves will be frequency modulated in accordance with the speech signals, without any amplitude modulation.

It is, however, well known that the operation of a carbon microphone is non-linear, since the resistance varies more rapidly for outward excursions of the diaphragm than for inward excursions. This effect can be very conveniently corrected by suitable choice of the resistance T1 or T2 because as shown in Fig. 5 the steepness and shape of the characteristic curve relating the zero-phase-shift frequency to the value of P may be adjusted thereby until it is substantially the inverse of the corresponding microphone resistance characteristic.

Actually the two characteristic curves are not quite the same shape, but adequate compensation over a relatively wide frequency band is possible, so that practically undistorted frequency modulated waves will be obtained from the oscillator.

It may be pointed out that the variable resistance element may be used for a somewhat different purpose. Suppose a number of single frequency oscillators according to Fig. 11 have to be manufactured. Then, as is well known, the output frequency of the individual oscillators will vary within a certain small range on account of the unavoidable manufacturing variation of the elements which make up the circuit. By providing a single adjustable resistance 44 connected to tapping points on the resistances 38 and 46 determined in the manner explained, the frequency of each individual oscillator may be accurately set or trimmed by the simple adjustment of the element 44, which may then be locked if desired in any convenient manner. This forms a very inexpensive means of obtaining an accurate output frequency in a circuit employing elements made to commercial limits. This method of trimming the network may clearly be used whatever be the purpose for which the network is used. Networks such as these shown in Fig. 7 or 9 may be adjusted in the same way by providing a small trimming condenser for the element 23.

The variable element corresponding to 44 in Fig. 11 may be a semi-conducting device, such as a rectifier, which may be controlled by an adjustable voltage or current. Fig. 12 shows how the network of Fig. 2 may be arranged, using a rectifier 45 connecting the tapping points in the resistances 6 and 8. An additional resistance 46 is connected at one end to the junction point of the elements 6 and 8, and at the other end to a terminal 47. A direct current source of adjustable voltage (not shown) is intended to be connected with its positive terminal to terminal 41 and its negative terminal to terminal 4. As is well known, the effective resistance of the rectifier 45 will depend on the applied voltage, the adjustment of which will change the zero-phase-shift frequency accordingly. This provides a convenient means of remote control of the network. If the network be used as part of an oscillator circuit similar to that shown in Fig. 11 for example, the oscillation frequency may be conveniently controlled in this way. If the source connected to terminals 4 and 41 includes a source of signal voltage, the arrangement provides an alternative means of frequency modulation of the oscillations. If the rectifier 45 is reversed, then the connections at terminals 4 and 41 to the direct current source should also be reversed.

Fig. 13 shows a variation of Fig. 12 in which a bridge rectifier 48 is used instead of the single rectifier 45. In this case an extra resistance corresponding to 46 is not needed. One pair of diagonal terminals of the bridge rectifier are respectively connected to the taps on the resistances 6 and 8, and the other pair to two terminals 49 and 59, to which a direct current

source (not shown) should be connected. This source may include a source of modulating signal voltage when the network is used in an oscillator circuit, as in the case of Fig. 12.

Another convenient method of controlling the zero-phase-shift frequency of a network such as any of those covered by Fig. 4 is to replace the resistance IE, or part of it, by the resistance element of an indirectly heated thermistor, the heating coil of which is connected to a source of adjustable direct or alternating current.

It will be evident that any of the networks covered by Fig. 4 may be provided with a rectifier arranged as in Fig. 12 or 13, and any such networks may be used in oscillator circuits similar to that shown in Fig. 11, or in any other manner.

What is claimed is:

1. A phase shift network of the L-type havin a series and a shunt arm; the series arm comprising a capacitor and a resistor connected thereto, the shunt arm comprising a capacitor, and a resistor in parallel therewith; means for controlling the frequency at which the network provides zero phase shift consisting essentially of an additional resistor having one terminal connected to an intermediate point of said series arm resistor and the other terminal connecting to an intermediate point of said shunt arm resistor.

2. A phase shifting network of the L -type having a series and a shunt arm; each of said arms comprising a resistor and a reactive member connected thereto; means for controlling the frequency at which the network provides zero phase shift consisting essentially of an impedance member having one terminal connected to an intermediate point of a member in said series arm and the other terminal connected to an intermediate point of a member in said shunt arm, said impedance member and said members to which it is connected presenting the same type impedance.

T 3. A phase shifting network of the L.type having a series arm and a shunt arm; each of said arms comprising a resistor and a reactive member connected thereto; means for controlling the frequency at which the network provides zero phase shift consisting essentially of a reactance member having one terminal connected to an intermediate point of a reactive member in said series arm and the other terminal connected to an intermediate point of a reactive member in said shunt arm, said reactance member and said reactive members to which it is connected presenting the same type reactance.

4. A phase shifting network according to claim 2f ,wherein the members in each of said arms comprise a delta formation, and said impedance member is connected between the apices of the deltas.

"5 A phase shifting network according to claim 2 wherein the impedance member is a rectifier and the members to which the impedance member is connected are resistors.

6. A phase shiftin network according to claim 3 in which said reactance member and said reactive members to which the reactance member is connected are capacitors.

EDMUND RAMSAY WIGAN.

REFERENCES CITED The following references are of record in the file of this patent:

UNITED STATES PATENTS Number Name Date 1,442,781 Nichols Jan. 16, 1923 2,043,345 Bobis June 9, 1936 2,072,946 Farnham Mar. 9, 1937 --2,093,665 Tellegen Sept. 21, 1937 2,173,427 Scott Sept. 19, 1939 2,236,985 Bartelink Apr. 1, 1941 2,294,863 Hadfield Sept. 1, 1942 2,298,177 Scott Oct. 6, 1942 2,300,632 Poch Nov. 3, 1942 1 2,418,842 Kinsburg Apr. 15, 1947 FOREIGN PATENTS Number Country Date 839,492 France Jan. 4, 1939

PATENT CITATIONS

Cited Patent	Filing date	Publication date	Applicant	Title
US1442781 *	7 Jul 1921	16 Jan 1923	Western Elec	Reamplifying- system
US2043345 *	6 Mar 1934	9 Jun 1936	Bell Telephone Labor Inc	Wave transmission network
US2072946 *	17 Oct 1935	9 Mar 1937	Rca Corp	Harmonic analyzer
US2093665 *	27 Jan 1934	21 Sep 1937	Rca Corp	Star and delta connection of impedances
US2173427 *	30 Aug 1937	19 Sep 1939	Gen Radio Co	Electric oscillator
US2236985 *	28 Oct 1939	1 Apr 1941	Gen Electric	Oscillator
US2294863 *	29 Mar 1941	1 Sep 1942	Associated Electric Lab Inc	Electrical storage and delay circuits
US2298177 *	25 May 1939	6 Oct 1942	Gen Radio Co	Electric filter circuit
US2300632 *	22 Jun 1940	3 Nov 1942	Rca Corp	Oscillation generator
US2418842 *	4 Mar 1943	15 Apr 1947	Bell Telephone Labor Inc	Scanning oscillator
FR839492A *				<i>Title not available</i>

* Cited by examiner

REFERENCED BY

Citing Patent	Filing date	Publication date	Applicant	Title
US2902656 *	30 Apr 1956	1 Sep 1959	Bell Telephone Labor Inc	Variable-frequency oscillator
US2965860 *	1 Nov 1957	20 Dec 1960	Telecomputing Corp	Flat phase network
US3070757 *	16 Mar 1960	25 Dec 1962	Avco Corp	Stable transistor r-c oscillator

Citing Patent	Filing date	Publication date	Applicant	Title
US3478269 *	4 Nov 1964	11 Nov 1969	Continental Electronics Mfg	Directional antenna signal combining arrangement and phase shifters therefor
US3739300 *	7 Mar 1972	12 Jun 1973	Tyre R	Single component controlled rc bridge
US3753140 *	7 Sep 1971	14 Aug 1973	Wandel & Goltermann	Equalizing network

* Cited by examiner

CLASSIFICATIONS

U.S. Classification	333/139 , 331/141 , 331/136 , 332/138 , 331/135
International Classification	H03H7/20 , H03H7/00
Cooperative Classification	H03H7/20
European Classification	H03H7/20

[Google Home](#) - [Sitemap](#) - [USPTO Bulk Downloads](#) - [Privacy Policy](#) - [Terms of Service](#) - [About Google Patents](#) - [Send Feedback](#)

Data provided by IFI CLAIMS Patent Services